

YAGI ANTENNA

150-175 MHz

BDA-YDAxxxxxx-7-1

Product Features

- Superior Performance
- All Weather Operation
- Aluminum Alloy Elements
- Pole Mounting Kits



Electrical Specifications	YDA150160	YDA155165	YDA165175
Frequency Range	150-160 MHz	155-165 MHz	165-175 MHz
Bandwidth	10 MHz	10 MHz	10 MHz
Elements	4	4	4
F/B Ratio	> 13 dB	> 13 dB	> 13 dB
Gain	7 dBi	7 dBi	7 dBi
VSWR	≤2.0	≤2.0	≤2.0
Polarization	Vertical or Horizontal	Vertical or Horizontal	Vertical or Horizon.
Horizontal Beamwidth	58°	58°	58°
Vertical Beamwidth	50°	50°	50°
Input Impedance	50 Ω	50 Ω	50 Ω
Max. Input Power	100 W	100 W	100 W
Lightning Protection	DC Ground	DC Ground	DC Ground
Mount way	Pole	Pole	Pole
Diameter of Installation Pole	Ø1.18~Ø1.96 in	Ø1.18~Ø1.96 in	Ø1.18~Ø1.96 in

Mechanical Specifications	Value
Connector	N Female
Dimensions	120cm length
Weight	1.80 kg
Radome Material	Aluminum Alloy
Operating Temperature	-40°C to +65 °C

DOC HON-62093.01 - 02122021 - DMC

Honeywell Business Solutions
 715 Peachtree Street NE
 Atlanta, GA 30308
 www.honeywell.com

HON-62093.01 • 02122021
 ©2021 by Honeywell International Inc. All rights reserved.
 Unauthorized use of this document is strictly prohibited.
 This document is not intended to be used for installation purposes. We try to keep
 our product information up-to-date and accurate. We cannot cover all specific
 applications or anticipate all requirements. All specifications are subject to change
 without notice.
 Country of origin: U.S.A.

**THE
 FUTURE
 IS
 WHAT
 WE
 MAKE IT**

Honeywell