

# FIBER GLASS OMNI ANTENNA 150 - 175 MHz

**BDA-FA-150175-2-1**

## Product Features

- Omni Fiberglass Antenna
- Max Power 100W
- Fiberglass



Electric Specifications	Value
Frequency Range	150-175 MHz
Bandwidth	8MHz
Gain	2.5 dBi
VSWR	≤1.90
Polarization	Vertical
Vertical Beamwidth	62°
Input Impedance	50 Ω
Max. Input Power	100 W
Lightning Protection	DC Ground

Mechanical Specifications	Value
Connector	N Male
Dimensions	120cm length
Support Pole Diameter	φ35-φ50(mm)
Weight	1.0 kg
Reflector Material	Aluminum
Radome Material	Fiberglass
Operating Temperature	-40°C to +65°C
Rated Wind Velocity	60 m/s

DOC HON62106.00 - 11272020 - D/M/C

**Honeywell Business Solutions**  
715 Peachtree Street NE  
Atlanta, GA 30308  
www.honeywell.com

HON62106.00 • 11272020  
©2020 by Honeywell International Inc. All rights reserved.  
Unauthorized use of this document is strictly prohibited.  
This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.  
Country of origin: U.S.A.

**THE  
FUTURE  
IS  
WHAT  
WE  
MAKE IT**

**Honeywell**